



HP LFD FLOOD LIGHT 400W - 1000W

DESCRIPTION

High efficiency LED COB flood light, built with a solid aluminum chassis for maximum thermal efficiency and delivering up to 140 lm / watt. With a built-in premium LED driver, the unit is easily wired direct to 240V mains power.

The HP COB series of LED flood lights is available from 400W up to 1000W.



100000hrs lifetime
Engineered reflector design
Sleek efficient design
High uniform illumination
Bridgelux LED Chip
High operating temperature range
Strong Mounting point



High efficiency, high output lumen No excessive heat output LED Up to 80% savings in energy Voltage range 180V - 265V Working Temp range -40~ + 60°C

APPLICATION

General commercial area lighting, carparks, sports fields, etc.

SPECIFICATION

Product Code	Voltage	Wattage (W)	Power Factor	Luminous Flux (Lm)	Beam Angle	Colour temp	IP Rating	Dimension
B0701-X-400W	180-265V AC	400W	0.92	48000	90	5500 (CW)	65	52.3*32.4*18.5cm
B0701-X-500W	180-265V AC	500W	0.92	60000	90	5500 (CW)	65	66.8*32.4*19.4cm
B0701-X-600W	180-265V AC	600W	0.92	72000	90	5500 (CW)	65	80.6*32.4*19.4cm
B0701-X-800W	180-265V AC	800W	0.92	96000	90	5500 (CW)	65	94.8*32.4*19.4cm
B0701-X-1000W	180-265V AC	1000W	0.92	120000	90	5500 (CW)	65	Design dependant

Note; This product range is normally pre order only





